

# Dual Monitor Arm Comparison Chart

|  |  |               |  |  |  |
|---|---|--|--|---|---|
| Zilker Dual Monitor Arm   | Range Dual Monitor Arm  | Crestview Dual Monitor Arm   | Crestview Align Dual Monitor Arm   | Moontower Dual Monitor Arm  | Enfield Dual Monitor Arm  |
| MON002  | MON021  | MON032   | MON033   | MON052  | MON042  |
|  |  |               |  |  |  |
| 15 year warranty  | 15 year warranty  | 15 year warranty   | 15 year warranty   | 15 year warranty  | 15 year warranty  |
| Slim, attractive design   | Dual long reach   | USB Kit add-on option<br>Holds lighter/heavier monitors  | USB Kit add-on option<br>Move and keep monitors in line with one motion            | Simple, economic  | Elegant, modern design with spring tension indicator                                |
| Weight capacity: 4.4 to 11 lb per arm   | Weight capacity: 4.5 to 17.5 lb per arm   | Weight capacity: 2.2 to 33 lb per arm  | Weight capacity: 2.2 to 17.6 lb per arm  | Weight capacity: 17.6 lb per arm  | Weight capacity: 4.4 to 19.8 lb per arm   |
| 39.5" Max Monitor Size*   | 52" Max Monitor Size*   | 35" Max Monitor Size*  | 32" Max Monitor Size*  | 27" Max Monitor Size*   | 32" Max Monitor Size*   |
| Clamp mount:<br>Compatible with 0.75" to 3.75" thick desktops                     | Clamp mount:<br>Compatible with 0.75" to 3.75" thick desktops                     | Clamp mount:<br>Compatible with 0.4" to 3.3" thick desktops                                    | Compatible with<br>Compatible with 0.4" to 3.3" thick desktops                     | Clamp mount:<br>Compatible with 0.4" to 3.4" thick desktops                         | Clamp Mount:<br>Compatible with 0.4" to 3.3" thick desktops                         |
| Bolt-through mount:<br>Compatible with 0.6" to 2.1" thick desktops                | Bolt-through mount:<br>Compatible with 0.6" to 2.1" thick desktops                | Bolt-through mount:<br>Compatible with 0.4 to 1.8" thick desktops                              | Bolt-through mount:<br>Compatible with 0.4 to 1.8" thick desktops                  | Bolt-through mount:<br>Compatible with 0.4 to 3.4" thick desktops                   | Bolt-Through Mount:<br>Compatible with 0.4 to 3.1" thick desktops                   |
| VESA compatibility:<br>75mm and 100mm<br>Quick release                            | VESA compatibility:<br>75mm and 100mm<br>Quick release                            | VESA compatibility:<br>75mm and 100mm<br>Quick release   | VESA compatibility:<br>75mm and 100mm<br>Quick release                             | VESA Compatibility:<br>75mm and 100mm   | VESA compatibility:<br>75mm and 100mm<br>Quick release                              |
| Clamp or bolt-through mount (both included)                                       | Clamp or bolt-through mount (both included)                                       | Clamp or bolt-through mount (both included)  | Clamp or bolt-through mount (both included)  | Clamp or bolt-through mount (both included)   | Clamp or bolt-through mount (both included)   |
| Mechanical spring   | Gas spring  | Gas spring   | Gas spring   | Pole mounted  | Mechanical spring   |
| Height range:<br>6.75" to 19" **  | Height range:<br>4.75" to 21" **  | Height range:<br>10" to 23" **   | Height Range:<br>10.4" to 23.4" **   | Height range:<br>2.8" to 16.9" **   | Height range:<br>8.7" to 18.5" **   |
| 12.25" vertical height adjustment   | 16.25" vertical height adjustment   | 13" vertical height adjustment   | 13" vertical height adjustment   | 14.1" vertical height adjustment  | 9.8" vertical height adjustment   |
| 20.5" max forward reach***  | 26.6" max forward reach***  | 23.5" max forward reach***   | 24.8" max forward reach***   | 17.6" max forward reach***  | 21.1" max forward reach***  |
| Side extension: 19.75" ****   | Side extension: 26" ****  | Side extension: 22.2" ****   | Side extension: 35.8" ****   | Side extension: 14.4" ***   | Side extension: 20" ****  |
| Collapses down to 3.6"  | Collapses down to 4.5"  | Collapses down to 4.6"   | Collapses down to 5.25" (9.25" with handle)  | Collapses down to 6"  | Collapse down to 4.6"   |
| Swivel of arm at base:<br>360°, 180°  | Swivel of arm at base:<br>360°, 180°  | Up to 270° swivel per arm  | Swivel of arm at base:<br>360°, 180°   | Swivel of arm at base:<br>180°  | Swivel of arm at base:<br>360°, 180°  |
| Monitor tilt range:<br>60° (+/-30°)   | Monitor tilt range:<br>160° (+90°/-70°)   | Monitor tilt range:<br>90° (+/-45°)  | Monitor tilt range:<br>20° (+/-10°)  | Monitor tilt range:<br>90° (+/- 45°)  | Monitor tilt range:<br>80° (+/- 40°)  |
| Monitor pan range:<br>180° (+/-90°)   | Monitor pan range:<br>180° (+/-90°)   | Monitor pan range:<br>180° (+/-90°)  | Monitor pan range:<br>20° (+/-10°)   | Monitor pan range:<br>180° (+/-90°)   | Monitor pan range:<br>180° (+/-90°)   |
| Monitor rotation: 360°  | Monitor rotation: 360°  | Monitor rotation:<br>180° (+/-90°)   | Monitor rotation: 360°   | Monitor rotation: 360°  | Monitor rotation: 360°  |
| Packaging dimensions:<br>17.1" x 12.4" x 5.4                                      | Packaging dimensions:<br>23.1" x 14.1" x 5.9"                                     | Packaging dimensions:<br>25.4" x 14" x 4.7"  | Packaging dimensions:<br>35.2" x 8.9" x 5.9"                                       | Packaging dimensions:<br>27.1" x 7.6" x 5.9"  | Packaging dimensions:<br>17.5" x 13.2" x 5"   |
| Weighs 9.8 lb with clamp, 8.6 lb with bolt-through                                | Weighs 20.5 lb with clamp, 17.9 lb with bolt-through                              | Weighs 18.1 lb with clamp, 16.1 lb with bolt-through   | Weighs 15.1 lb with clamp, 12.9 lb with bolt-through                               | Weighs 10.2 lb with clamp, 9 lb with bolt-through                                   | Weighs 9.5 lb with clamp, 8.5 lb with bolt-through                                  |
| Bolt hole diameter:<br>0.4" to 3.2"   | Bolt hole diameter:<br>0.4" to 3.2"   | Bolt hole diameter:<br>One hole: 2.2" to 3.1" Two holes: 0.4" to 1.3" each, spaced 1.7" apart" | Bolt hole diameter:<br>0.4" to 3.1"  | Bolt hole diameter:<br>0.4" to 3.1"   | Bolt hole diameter:<br>0.4" to 3.1"   |

\* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

\*\* Height range measured from desk surface to center of monitor mount

\*\*\* Max forward reach measured from center of post to VESA plate

\*\*\*\* Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate