








































Power and Data Comparison Chart

							
Clamp-On or Under-Mount Power with USB PDC003	4-Outlet Mountable Surge Protector PDC015	8-Outlet Mountable Surge Protector PDC006	Power Hub with USB PDC010	4-Port USB 3.0 Hub ACC013	Power Grommet PDC002	Power Tower PDC009	Pop Up Power Grommet PDC013
Colors: 	Colors: 	Colors: 	Colors: 	Colors: 	Colors: 	Colors: 	Colors: 
5.5" W x 2.7" D x 2" H (3.7" H with Clamp mount)	11.43" W x 1.8" D x 1.5" H (not including mounting brackets)	17.25" W x 2.2" D x 1.25" H (not including mounting brackets)	5.75" W x 4" D x 1.5" H	3" W x 1.63" D x 0.45" H	3.72" OD x 2.6" H	5.9" W x 5.9" D x 23.1" H	"3.63"" OD x 9.25"" (down) 3.63"" OD x 12.38"" (up)"
Number of outlets: 2	Number of outlets: 4	Number of outlets: 8	Number of outlets: 2	Number of outlets: 0	Number of outlets: 2	Number of outlets: 2	Number of outlets: 4
Number of USB Ports: 2	Number of USB Ports: 2	Number of USB Ports: 0	Number of USB Ports: 4	Number of USB Ports: 4	Number of USB Ports: 2	Number of USB Ports: 2	Number of USB Ports: 2
USB Capability: 5V 2.1A shared USB output for charging	USB Capability: USB-A, 5V/2.1A shared output for charging	USB Capability: N/A	USB Capability: 5V 4.8A shared USB output for charging	USB Capability: USB 1.1, 2.0, and 3.0 compatible for data transfer and limited charging	USB Capability: N/A	USB Capability: 5V/2.1A shared output for charging	USB Capability: PD20W max Each USB-A: 9V/2A, 12V/1.5A Single USB-C: 9V/2.22A, 12V/1.67A All USB-A & USB-C together: 5V/3
Input Voltage: 120V, 12A	Input Voltage: 120V, 12A	Input Voltage: 120V, 15A	Input Voltage: 120V, 13A	Input Voltage: N/A	Input Voltage: 120V, 15A	Input Voltage: 120V, 12A	Input Voltage: 120V, 15A
Cord Length: 6'	Cord Length: 10'	Cord Length: 10'	Cord Length: 5'	Cord Length: 5.75'	Cord Length: 10'	Cord Length: 10'	Cord Length: 5'
 ETL listed for US and Canada	 ETL listed for US and Canada	 ETL listed for US and Canada	 ETL listed for US and Canada	N/A	 UL listed for US and Canada	 ETL listed for US and Canada	 ETL listed for US and Canada
Clamp-on and under-mount	Mounts to desktop or V2 & V2-commercial desk frame mounting points	Mounts to desktop or V2 & V2-commercial desk frame mounting points	Freestanding	Freestanding	Fits in desktop grommet hole	Floor Standing	Fits in desktop grommet hole
 No wireless charging	 No wireless charging	 No wireless charging	 No wireless charging	 No wireless charging	 No wireless charging	 No wireless charging	 Wireless charging
 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns	 15 year warranty Free Shipping Free Returns