

Triple, Quad, and Six Monitor Arm Comparison Chart



Crestview Align Triple Monitor Arm



Moontower Triple Monitor Arm



Moontower Quad Monitor Arm



Moontower Six Monitor Arm

MON034	MON053	MON054	MON056
15 year warranty	15 year warranty	15 year warranty	15 year warranty
USB Kit add-on option Move and keep monitors in line with one motion	Simple, economic	Simple, economic	Simple, economic
Weight capacity: 2.2 to 13.2 lb per arm	Weight capacity: 17.6 lb per arm	Weight capacity: 17.6 lb per arm	Weight capacity: 14.3 lb per arm
27" Max Monitor Size*	27" Max Monitor Size*	27" Max Monitor Size*	27" Max Monitor Size*
Clamp mount: Compatible with 0.4" to 3.3" thick desktops Bolt-through mount: Compatible with 0.4 to 1.8" thick desktops	Compatible with 0.4" to 3.4" thick desktops	Compatible with 0.4" to 3.4" thick desktops	Compatible with 0.4" to 3.4" thick desktops
VESA Compatibility: 75mm and 100mm Quick Release	VESA Compatibility: 75mm and 100mm	VESA Compatibility: 75mm and 100mm	VESA Compatibility: 75mm and 100mm
Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)	Clamp or bolt-through Mount (both included)
Gas Spring	Pole Mounted	Pole Mounted	Pole Mounted
Height Range: 10.4" to 23.4" **	Height Range: 2.8" to 16.9" **	Height Range: 2.8" to 29.1" **	Height Range: 2.8" to 29.1" **
13" vertical height adjustment	14.1" vertical height adjustment	26.3" vertical height adjustment	26.3" vertical height adjustment
24.8" max forward reach***	29.5" max forward reach***	17.6" max forward reach***	29.5" max forward reach***
Side extension: 47.5" ****	Side extension: 26.3" ****	Side extension: 14.4" ****	Side extension: 26.3" ****
Collapses down to 5.25" (9.25" with handle)	Collapses down to 6"	Collapses down to 6"	Collapses down to 6"
Swivel of arm at base: 360°, 180°	Swivel of arm at base: 180°	Swivel of arm at base: 180°	Swivel of arm at base: 180°
Monitor tilt range: 20° (+/-10°)	Monitor tilt range: 90° (+/- 45°)	Monitor tilt range: 90° (+/- 45°)	Monitor tilt range: 90° (+/- 45°)
Monitor pan range: 20° (+/-10°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)	Monitor pan range: 180° (+/-90°)
Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 360°	Monitor rotation: 360°
Packaging dimensions: 24.5" x 12.6" x 5.7"	Packaging dimensions: 32.4" x 7.6" x 5.9"	Packaging dimensions: 31.2" x 11.1" x 5.9"	Packaging dimensions: 31" x 14" x 5.9"
Weighs 18 lb with clamp, 15.9 lb with bolt-through	Weighs 13.6 lb with clamp, 12.4 lb with bolt-through	Weighs 17.1 lb with clamp, 15.9 lb with bolt-through	Weighs 24 lb with clamp, 22.8 lb with bolt-through
Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"	Bolt hole diameter: 0.4" to 3.1"

* With monitor at back of desk, max monitor width will decrease as the arms are pulled forward

** Height range measured from desk surface to center of monitor mount

*** Max forward reach measured from center of post to VESA plate

**** Side extension is how far the monitor arm can extend out to the left or right. It is measured from the center of the post/base to the center of the VESA plate